

## Tabla Comparativa de Proyectoros EPSON serie EB4XX

	Epson EB-440W	Epson EB-450W	Epson EB-460	Epson EB-450Wi	Epson EB-460i
<b>SPECIFICATION</b> Projection system (3LCD) Native resolution Native aspect ratio Resolution supported White Light Output* (Brightness) Colour Light Output*	0.59" with MLA (x3) polysilicon TFT active matrix WXGA 16:10 Up to 1080i 2200 lm/1540 lm (normal/eco-mode) 2200 lm/1540 lm (normal/eco-mode)	0.59" with MLA (x3) polysilicon TFT active matrix WXGA 16:10 Up to 1080i 2500 lm/1740 lm (normal/eco-mode) 2500 lm/1740 lm (normal/eco-mode)	0.63" with MLA (x3) polysilicon TFT active matrix XGA 4:3 Up to 1080i 3000 lm/2080 lm (normal/eco-mode) 3000 lm/2080 lm (normal/eco-mode)	0.59" with MLA (x3) polysilicon TFT active matrix WXGA 16:10 Up to 1080i 2500 lm/1740 lm (normal/eco-mode) 2500 lm/1740 lm (normal/eco-mode)	0.63" with MLA (x3) polysilicon TFT active matrix XGA 4:3 Up to 1080i 3000 lm/2080 lm (normal/eco-mode) 3000 lm/2080 lm (normal/eco-mode)
<b>PROJECTION LENS</b> F-number Focal length Zoom ratio Offset	1.80 4.68 mm Digital zoom 1-1.35 4.57:-1	1.80 4.68 mm Digital zoom 1-1.35 4.57:-1	1.80 4.68 mm Digital zoom 1-1.35 7.67:-1	1.80 4.68 mm Digital zoom 1-1.35 4.57:-1	1.80 4.68 mm Digital zoom 1-1.35 7.67:-1
<b>LAMP</b> Type Life	230 W UHE – E-TORL 2,500 hours/3,500 hours (normal/eco-mode)				
<b>IMAGE</b> Colour reproduction Contrast ratio* Keystone correction	Full-colour (16.77 million colours) 2,000:1 Vertical: ±5°				
<b>VISUAL INPUT</b> Computer Video USB flash drive Epson USB Visualiser	2 x D-sub 15-pin (RGB), 1 x USB 2.0 type B 1 x RCA, 1 x S-Video, 2 x Component (D-sub 15-pin) 1 x USB 2.0 type A 1 x USB 2.0 type A				
<b>VISUAL OUTPUT</b> Monitor	1 x D-sub 15-pin				
<b>AUDIO INPUT</b> Computer Video Microphone	2 x Stereo mini-jack 1 x RCA (White/Red) 1 x Stereo mini-jack				
<b>AUDIO OUTPUT</b> Computer	1 x Stereo mini-jack				
<b>CONTROL</b>	1 x LAN (RJ45), 1x RS-232C (D-sub 9-pin)				
<b>WIRELESS CONNECTION</b>	Optional wireless				
<b>EASY INTERACTIVE FUNCTION</b>	N/A	N/A	N/A	1 x Easy Interactive Pen	1 x Easy Interactive Pen
<b>ADVANCED FEATURES</b>	Quick start, instant off, source search, 8 colours mode, e-zoom, A/V mute, freeze				
<b>SECURITY</b>	Padlock and security cable hole, Kensington lock hole, password protection, wireless LAN unit lock				
<b>DIRECT POWER ON/OFF</b>	Yes				
<b>POWER REQUIREMENTS</b> Power supply wattage Power consumption lamp on Power consumption standby	100 – 240 V AC +/- 10%, 50/60 Hz 343W/257W (normal/eco mode) 12W/0.3W (network on/network off)				
<b>OPERATING TEMPERATURE/ALTITUDE</b>	0 °C to 35 °C/0 m to 2286 m				
<b>GENERAL</b> Weight Dimension (DxWxH)	5.7 kg 481x369x115 mm	5.7 kg 481x369x115 mm	5.7 kg 481x369x115 mm	5.8 kg 481x369x115 mm	5.8 kg 481x369x115 mm
<b>FAN NOISE</b>	35 dB/28 dB (Normal/Eco)				
<b>ON-SCREEN MENU</b>	English/French/German/Italian/Spanish/Portuguese/Russian/Swedish/Norwegian/Finnish/Danish/Bulgarian/Dutch/Polish/Hungarian/Czech/Slovak/Romanian/Croatian/Slovenian/Ukrainian/Greek/Turkish/Arabic/Hebrew/Japanese/Simplified Chinese/Traditional Chinese/Korean/Catalan/Thai/Indonesian/Malay/Vietnamese				
<b>SUPPLIED ACCESSORIES</b>	Power cable 4.5 m, remote control + batteries, bundled software, password protected sticker, user manual, setting plate	Power cable 4.5 m, remote control + batteries, bundled software, password protected sticker, user manual, setting plate	Power cable 4.5 m, remote control + batteries, bundled software, password protected sticker, user manual, setting plate	USB cable 5 m, easy interactive pen power cable 4.5 m, remote control + batteries, bundled software, password protected sticker, user manual, setting plate	USB cable 5 m, easy interactive pen Power cable 4.5 m, remote control + batteries, bundled software, password protected sticker, user manual, setting plate
<b>SAFETY REGULATIONS</b>	EMC directive (2004/108/EC) CE marking GOST®				
<b>WARRANTY</b>	2 years on main unit, 1 year on lamp				

\* ISO 21118 based measurement